



CHING MARS CORPORATION

10F. NO. 502, DA-AN ROAD, SHU LIN CITY, NEW TAIPEI CITY, TAIWAN

TEL: 886-2-86873877

FAX: 886-2-86873833


E-Mail: sales@chingmars.com.tw

Web: http://www.chingmars.com.tw


1.0 BRAND:	NO BRAND
-------------------	----------

2.0 PRODUCT DESCRIPTION (from SYSPRO):	
CAX-69D-S	LED STROBE LIGHT 12/24VDC AMBER
CAX-69-RS	LED STROBE & ROTATING LIGHT 12/24VDC AMBER

3.0 PRODUCT PHOTO(S):	NOTE: Product images are shown for <u>display purposes only</u> and may not be representative of the final product. The product is to be built according to the specific requirements listed in Sections 4.0 through 11.0 below.
------------------------------	--



CAX-69D-S



CAX-69-RS

4.0 PRODUCT REQUIREMENTS:

4.1 Key Product Attributes (Special characteristics, features, design, style, etc. that the product must have. Examples: cord-reinforced rubber, NSD certified for use in wet locations, permanently lubricated bearings)

- Din type or Flat surface mount with screws, 12/24VDC, Hi-power 3W LED.



CHING MARS CORPORATION

10F. NO. 502, DA-AN ROAD, SHU LIN CITY, NEW TAIPEI CITY, TAIWAN

TEL: 886-2-86873877

FAX: 886-2-86873833

E-Mail: sales@chingmars.com.tw

Web: http://www.chingmars.com.tw

4.2 Properties & Performance (Include tolerances and any reliability requirements. Provide illustrations, as necessary, to indicate measurement locations)	Requirement	
Sku	CAX-69D-S	CAX-69-RS
Mounting Type	Din type	Flat surface mount with screws
Overall Dome diameter	152.5mm	152.5mm
Overall Base diameter	162.5mm	162.5mm
Overall Height	Please see above.	160mm
Light source/lamp style	Hi-power LED 3W x 12PCS	
Lamp life	20000 hrs	
Operating temperature (°F)	-40 to 185	
Voltage	12/24 VDC	
Operating Current	2.5A(Max) amps	
Dome Color	Amber	Amber
Dome material	Polycarbonate	Polycarbonate
Base color	Ivory white & Black	Ivory white
Base material	PC & Black Rubber	PC
Flash Patterns	Triple flashes	Single, double, triple, quad, quint and rotating
Wire leads	18 AWG, 105 °C 600V	18 AWG, 105 °C 600V
Wire leads color	Red (VCC), Black(GND)	Red(VCC), Black(GND), Blue(SW)
Routing of wire leads	Through bottom of the unit	Through bottom of the unit
Hardware kit	N/A	8mm wash*3, spring wash*3, nut*3
Approval	ECE R65	
Environmental Ratings	Indoor/Outdoor Use, IP 66	